

# A410



## Product description

---

TransferRite® A410 is a low tack application tape featuring a high grade saturated paper backing with specially formulated latex, pressure sensitive adhesive.

## Applications

---

Can be used in sign shops for general purpose use as pre-space and decal transfer. Pre-spacing tape is designed to assist in the application and transfer of pressure sensitive decals that have been cut into letters and legends. A410 is recommended for die cut logos and is best used for one-piece lettering bigger than 31cm.

## Technical information

Paper thickness (without adhesive)	83 µm
Adhesive thickness	25 µm
Total thickness	108 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	2.6 N/25mm (low tack)
Core colour	green
Tensile strength	88 N/25mm
Elongation at break	3%
Shelf life (from time of manufacture)	30 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Laanakkerweg 12  
4131 PA Vianen  
*tel.* 0347 - 366 711  
*fax* 0347 - 366 712  
*e-mail* info@tripa.nl  
*internet* www.tripa.nl

