

# A610



## Product description

TransferRite® A610 is a high tack application tape featuring a lightweight saturated paper backing with specially formulated latex, pressure sensitive adhesive for general-purpose use as pre-space and application tapes.

## Applications

Can be used in sign shops for general purpose use as pre-space and decal transfer. Pre-spacing tape is designed to assist in the application and transfer of pressure sensitive decals that have been cut into letters and legends. A510 is recommended for die cut logos and is best used for one-piece lettering smaller 5 cm.

## Technical information

Paper thickness (without adhesive)	82 µm
Adhesive thickness	25 µm
Total thickness	107 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	2.9 N/25mm (high tack)
Tensile strength	88 N/25mm
Elongation at break	3%
Shelf life (from time of manufacture)	30 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.