

EMBLEM Floorgraphics III

EMBLEM FLOGRA3 is a structured laminate for the guarding of prints at POS advertising with anti reflex surface. The waterbased adhesive is characterized by high color neutrality and UV resistance. The structured surface of the film assures a anti-slip protection and has a low level of soiled.

Matchcode:	FLOGRA3
Material:	PVC, monomeric
Finish:	matt embossed
Colour:	transparent
Thickness:	120 μ m
Liner:	clay coated kraft paper, 120 g/m ² , siliconized
Adhesive:	transparency, poly-acrylate, permanent
Adhesion:	19 N / 25mm - acc. Finat1, 24h (average value)
Application temperature:	> +10 °C
Temperature resistance:	from -30 to +70 °C
Anti-Slip property:	R 9 acc. DIN 51130
Standard roll width:	105 cm, 137 cm
Standard roll length:	50 m
Lamination film:	face out
Storage:	at 20 °C / 50 % humidity, 2 years in original boxes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Floorgraphics III

Description:

EMBLEM Floorgraphics film III advertising stay bright for a longer time due to the less dirt pickup. That means powerful colours for a longer time. The structured surface of the film is tested acc. DIN 51130 and got a slide resistance of R9.

The permanent type of adhesive has been specially developed for protective laminates.

The lamination film is made for cold lamination processing and is characterized by a good moisture and UV resistance and very good optical properties.

The durability of a final laminated floor protection amounts up to 4 month if used properly. It can be shorter because many factors influence durability. The user should perform self-tests.

Processing:

This product is especially made for indoor use.

For an excellent lamination without silvering from the first minute we recommend warm lamination processing up to 50°C.

Typical Applications:

Finishing floor advertising, print finishing for popups, at POS.