



LEADING THE WAY

EMBLEM Solvent City WhiteBack

EMBLEM Solvent City WhiteBack is a matt, white barrier coated paper for solvent based inks. You can print on EMBLEM SOCWB with common eco-solvent, solvent, latex and UV-curable inks. Main fields of application are city light posters, photorealistic posters, indoor signs and short-term promotions and outdoor signage.

Matchcode:	SOCWB
Material:	barriercoated paper, waterresistant
Finish:	matt
Colour:	white
Weight:	135 g/m ²
Application temperature:	+10°C up to +30°C
Width of rolls:	42", 50", 54", 60", 64"
Length of rolls:	50 m
Durability:	3 month outdoor under condition of middle-european climate
Storage:	cool and dry environment, at 15-25°C, 50% rel. humidity
Shelf life:	24 month in original packing

COMPATIBLE INKS:

Eco Solvent:	yes	UV:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-99 50 · Telefax: +49 41 93-99 52 20
E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Solvent City WhiteBack

Description:

EMBLEM Solvent City WhiteBack is a matt, white barrier coated paper for solvent based inks. You can print on EMBLEM SOCWB with common eco solvent, solvent, latex and UV curable inks. The special coating permits a good ink saturation and brilliant colours. Little variations are possible because paper is a natural product.

Processing:

To achieve best water resistance give the print an open drying time of at least 10 hours before further processing.

For outdoor applications which have to last more than 10 to 12 weeks lamination is needed. Before lamination the prints have to be dried and fumigated completely otherwise there are risks to get bubbles between media and lamination film.

Application:

Main fields of application are city light posters, photorealistic posters, indoor signs and short-term promotions and outdoor signage.