

EMBLEM Solvent RollUp PP Film

EMBLEM Solvent RollUp PP Film

| | |
|----------------------|----------------------|
| Matchcode: | SOROPPF |
| Material: | Polypropylen |
| Finish: | semiglossy |
| Colour: | white |
| Weight (ISO 536): | 130 g/m ² |
| Thickness (ISO 534): | 170 µm |
| Opacity (TD-904): | 99 % |
| Storage Temperature: | 10° C - 30° C |
| Air Humidity: | 35 % - 65 % |
| Lamination: | cold |
| Width of roll: | 36" / 42" / 60" |
| Length of roll: | 30 m |
| Flame retardant: | no |
| Eco Solvent: | yes |
| Solvent: | yes |
| Latex: | yes |
| UV: | n.n. |

Printer compatibility (selection only):

Epson GS6000
HP Latex series, 8000S - 10000S
Roland Pro III-, SP-, VP-, RS- und VS-series
Mimaki JV 5, JV3 und JV33
Mutoh ValueJet, Osprey, Rockhopper I - III
Seiko IP6600

Description:

EMBLEM SOROPPF is a tear-resistant polypropylenfilm with a special coating for solvent and eco-solvent inks.

The coating allows brilliant photo quality printing, short drying time and high saturation. **SOROPPF** is fully waterproof and most scratch resistant.

With **SOROPPF** it is able to achieve high-end presentation quality with bright colours and very good contrast. The prints are featured by minor reflections. The back side of **SOROPPF** is grey coated. The high opacity allows an unlimited use as rollup film.

To avoid fingerprints it is advisable to wear cotton gloves.

Applications:

RollUp displays, signs for in- and outdoor, POS advertisement, photoreproduction, displays

Because of the great number of potential influences at object time and applinace of the above-mentioned materials, on which we have no bearing, test prints have to be effected by the user himself. A legally binding warranty can not be deduced from our specifications. Every liability and warranty that goes beyond the warranty of the product amounting to the product's value as well as entitlements to damages are excluded.