



LEADING THE WAY

EMBLEM Solvent Universal Decoration Media

EMBLEM Solvent Universal Decoration Media is based on a non-woven polyester. It has a smooth canvas like surface and is printable with common eco solvent, solvent, latex and UVC inks. Due to its low weight and good flatness, together with its high tensile resistance, non-woven polyester is suitable for multiple applications.

| | |
|--------------------------|--|
| Matchcode: | SOUDM |
| Material: | non-woven polyester |
| Finish: | semi matt |
| Colour: | white |
| Weight: | 210 g/m ² |
| Thickness: | 310 µm |
| Whiteness: | 105 acc. ASTM D1925 |
| Application temperature: | more than 15° C |
| Standard rolls width: | 36", 60" |
| Standard roll length: | 30 m |
| Durability: | up to 12 month outdoor under condition of Central European climate |
| Storage: | cool and dry environment, at 15-25°C, 50% rel. humidity |
| Shelf life: | 12 month in original packing |

COMPATIBLE INKS:

| | | | |
|--------------|-----|--------|-----|
| Eco Solvent: | yes | UVC: | yes |
| Solvent: | yes | Latex: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-9950 · Telefax: +49 41 93-995220
E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Solvent New

Description:

EMBLEM Solvent Universal Decoration Media is based on a non-woven polyester with a canvas embossing. Colour-intensive prints can be created on SOUDM with standard eco solvent, solvent, latex and UVC inks. Due to its low weight and good flatness, together with its high tensile resistance, non-woven polyester is suitable for multiple applications. It can be used as a canvas replacement for wedge frameworks, as there is no stress-whitening in the coating and it features high scratch resistance. Additionally, SOUDM is PVC-free.

Processing:

Before further processing the VOC's of solvent, eco-solvent and latex inks must be dried completely. The drying time depends on the amount of ink.

Before printing check the correct drying temperature by carrying out a trial print.

To avoid fingerprints the use of cotton-gloves is advisable.

Application:

Printing applications for SOUDM are stretcher frame, fine art, event banner, wallpaper, interior design, X-banner applications, roll-ups, fence anchoring, space divider, racing numbers for sports events and ceiling pendants.