

NEW



FLOOR Vinyl
by Gerflor

**THE PRINTABLE
FLOORING**

Dedicated to **communication events**
(stand, advertising, POS communication)
and **decoration items business**.

Printable, ideal to **personnalize** your floor.

Compatible with **UV large-size
digital printer, latex and
digital cutting solution**.

Gerflor
theflooringgroup

Made in France by Gerflor,
leader of professional and housing flooring solution
for more than 80 years.





EASY TO LAY:
indoor, with
double-sided adhesive,
on all subfloor
(wood, concrete, tile...)



**ECONOMIC AND
COMFORTABLE,**
absorbs noises
and shocks,
slip-resistant (R10)

FLOOR Vinyl

by Gerflor

ROLL WIDTH

1,5 M

2 M

3 M

DESCRIPTION

| | | | | |
|-----------------------------|-----------------------|-------|------|--|
| Total thickness | EN ISO 24346 (EN 428) | mm | 2.50 | |
| Wearlayer thickness | EN ISO 24340 (EN 429) | mm | 0.15 | |
| Weight / Mass per unit area | EN ISO 23997 (EN 430) | g/sqm | 1485 | |
| PU Surface treatment | - | - | no | |
| Mechanical embossing | - | - | yes | |

CLASSIFICATION

| | | | | |
|---|------------|-------|---------------------|--|
| Norm / Product specification | - | - | EN ISO 26986 | |
| Fire rating - Classification Glued down wood support | EN 13501-1 | class | C _{fl} -s1 | |
| Slip resistance wet : ramp test with oil | DIN 51 130 | class | R10 | |

PERFORMANCES

| | | | | |
|---|-------------------------|--------|--------|--|
| White index | WI-ASTM | % | ≥ 55 | |
| Wear Group | EN 660-2 | group | T | |
| Dimensional stability after exposure to heat | EN ISO 23999 (EN 434) | % | 0.05 | |
| Residual indentation (requirement) | EN ISO 24343-1 (EN 433) | mm | < 0.35 | |
| Colour fastness | EN 20 105-B02 | degree | > 6 | |

PACKAGING

| | | | | | |
|----------------------------------|-----------------------|----|----------------------------|-------------|------|
| Standard Length of sheet | EN ISO 24341 (EN 426) | ml | 30 | | |
| Minimum Length of sheet | EN ISO 24341 (EN 426) | ml | 15 | | |
| Cardboard Core diameter (inside) | - | mm | 100* ou 76,8* | | 100* |
| Total weight of a reel | - | kg | 67 | 90 | 134 |
| Total diameter of a reel | - | mm | 330 | | |
| Bulk transportation | - | - | yes | | |
| Pallet dimension | - | mm | in option (6 rolls/palett) | | no |
| | | | 1100 x 2000 | 1100 x 2000 | - |

ENVIRONMENT

| | | | | |
|----------------------|----------------|-------------------|-------|--|
| TVOC after 28 days | EN ISO 16000-6 | µg/m ³ | < 100 | |
| French norm | - | - | A+ | |
| Floorscore (US norm) | - | - | OK | |

MARQUAGE CE

| | | | | | | |
|----|----------|--|--|--|--|-----|
| CE | EN 14041 | | | | | R10 |
|----|----------|--|--|--|--|-----|

* Core diameter tolerance: -0,4 mm / +0,1 mm

