



# DigiFort® wall media NW350

Fabric backed non woven commercial wallcovering  
product sheet

## **General description:**

Non Woven backed wallcovering suitable for ink jet printing.

## **Roll specifications:**

Width:	130	cm.
Length:	50	lm.
Internal core diameter	7,6	cm
Packaging	In Kraft paper with* or without carton box	
* with surcharge		

## **Composition:**

Substrate weight:	60 ± 20 g/m <sup>2</sup>	EN ISO 2286-2
Vinyl weight	290 ± 20 g/m <sup>2</sup>	EN ISO 2286-2
Total weight	350 ± 20 g/m <sup>2</sup>	EN ISO 2286-2
Thickness	* mm	EN ISO 2286-3
* Depends on embossing / structure		

## **Printing inks:**

Suitable for Solvent, Eco Solvent, Latex and UV-curable

## **Properties:**

Coating Specially formulated acrylic laquer with exclusive ink jet properties.

## **Washability prior to printing:**

Scrubable EN 259 –2

**In general;** Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

## **Resistance to chemicals prior to printing:**

Resistant to: Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.  
Not resistant to: Solvents like Ketones; Esters; Aromatic hydrocarbons.

## **Installation:**

Refer to installation recommendations leaflet inside the core of each roll.

## **Adhesives:**

Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute.

## **Safety/Ecological:**

The material is classified as non-hazardous DIN 52900 or 91/155/EEG,2001/58/EC

## **Fire resistance:**

### **Fire rating**

Euro class	B s1d0
Class 0 / 1	BS 476 part 6/7
M1	NF P 92501 / 92507
B1	DIN 4102 – 01 *
* ABP Number : P-MPA-E-04-507	

## **Lightfastness:**

7 out of 8 International Woolscale BS EN 20105 / ISO 105-B02